

POWERLITE 8000

High-Energy pulsed Nd:YAG lasers
with excellent beam quality and versatility




MAIN FEATURES

- Up to 1.65 J @ 1064 nm
- Robust and field-proven technology
- Barium sulfate diffuser for improved beam uniformity and pump efficiency
- Flashlamp warranty up to 50 million shots for operation without downtime
- User-configurable harmonic modules for user-friendly wavelength switch
- Cables and cooling lines disconnectable for easy integration
- Intuitive GUI interface, laptop included
- SLM option (Single Longitudinal Mode) for long coherence length
- Optional chiller for use in any environment


MAIN APPLICATIONS

- LiDAR
- INSTRUMENTATION
- PLD
- DYE, OPO & Ti:Sa PUMPING
- SPECTROSCOPY
- LIF
- COMBUSTION

Typical beam profiles



Near field, 1.65 J @ 1064 nm, 10 Hz



Far field, 1.65 J @ 1064 nm, 10 Hz

Many options and configurations are available.
Please contact Lumibird to find the best match for
your needs and compatibility between options.

POWERLITE 8000

High-Energy pulsed Nd:YAG lasers
with excellent beam quality and versatility



SPECIFICATIONS

		8000	8010	8020	8030	8050
Repetition rate (Hz)		10		20	30	50
Energy per pulse (mJ)	1064 nm	1200	1650	1200	650	550
	532 nm	600 ⁽¹⁾ /800	800 ⁽¹⁾ /1100	550 ⁽¹⁾ /780	300 ⁽¹⁾ /420	210
	355 nm ⁽²⁾	310	450	300	150	95
	266 nm	120	150	80	50	30
Pulse duration (ns) ⁽³⁾	1064 nm	6 - 8			7 - 9	
	532 nm	5 - 7			6 - 8	
	355 nm	5 - 7			6 - 8	
	266 nm	5 - 7			6 - 8	
Beam diameter ⁽⁴⁾ (mm)	1064 nm	9			7	
Beam divergence ⁽⁵⁾ (mrad)	1064 nm	0.45			0.5	
Spatial profile @ 1064 nm ⁽⁶⁾	Horizontal near field ⁽⁷⁾	0.7				
	Far field ⁽⁸⁾	0.95				
Max deviation from fitted Gaussian ⁽⁹⁾ (± %)	Near field	40				
Polarization	1064 nm	Horizontal				
	532 nm	Vertical				
	355 nm	Horizontal				
	266 nm	Horizontal				

- (1) Using type II doubler
 (2) Using type I doubler
 (3) Measured at FWHM with fast photodiode and 1 GHz oscilloscope
 (4) At the output of the laser
 (5) Full angle, at 1/e² of the peak
 (6) Least square fit to Gaussian (perfect fit = 1)
 (7) Measured at 1 m from laser output
 (8) At focal plane of a 2 m focus lens
 (9) Within FWHM points near field at 1 meter

Pulse to pulse energy stability (%) ⁽¹⁰⁾	1064 nm	± 2.5 (0.8)	± 3 (1)	
	532 nm	± 3.5 (1.2)	± 4.5 (1.5)	
	355 nm	± 4 (1.3)	± 5 (1.7)	
	266 nm	± 10 (3.3)		
Power drift (%) ⁽¹¹⁾	1064 nm	± 3	± 5	
	532 nm	± 5	± 6	± 7
	355 nm	± 5	± 6	± 8
	266 nm	± 8	± 8	
Pointing stability (μrad) ⁽¹²⁾	All wavelengths	± 30		
Jitter @ 1064 nm (ns) ⁽¹³⁾	Standard	± 0.5		
	SLM	± 1		
Linewidth @ 1064 nm (cm ⁻¹)	Standard	1 ⁽¹⁴⁾		
	SLM	0.003 ⁽¹⁵⁾		

- (10) Peak to peak, 99% of the shots (RMS), on 200 consecutive shots
 (11) Over 8 hours for ΔT° ≤ ± 3°C
 (12) 99.9% shots will be < ± 30 μrad with ΔT room < ± 3°C
 (13) With respect to external trigger
 (14) Measured at FWHM with a grating spectrometer with 0.045 cm⁻¹ resolution
 (15) Measured at FWHM with a slow scan Fabry-Perot etalon



Photonic Solutions Ltd
 Edinburgh
 EH14 4AP
 +44 131 664 8122
www.photonicsolutions.co.uk

Many options and configurations are available.
 Please contact Lumibird to find the best match for
 your needs and compatibility between options.



POWERLITE 8000

High-Energy pulsed Nd:YAG lasers
with excellent beam quality and versatility

SPECIFICATIONS

OTHER INFORMATION

Power requirements		200 - 240 VAC, single phase, 50/60 Hz				
		8000	8010	8020	8030	8050
		10 A	11 A	16 A		17 A
Cooling (water to water)	GPM (gallons/minute) ⁽¹⁶⁾	1 - 2				
	Temperature ⁽¹⁷⁾	< 22° C / 70° F				
Operating temperature		18 to 30° C / 65 to 87° F				
Cable length		5 m (16.4 ft)				
Flashlamp warranty		50 million shots ⁽¹⁸⁾				


(16) at 10 - 40 PSI pressure drop

(17) higher flow rate for higher temperature


(18) 80% of energy, or 1 year, whatever comes first

Laser head

Dimensions in mm (inches)



Integrated cooling & electronics



DANGER
INVISIBLE LASER RADIATION
AVOID EYE OR SKIN EXPOSURE TO
DIRECT OR SCATTERED RADIATION
CLASS 4 LASER PRODUCT